

SAFETY DATA SHEET POLY BD RESIN PART B

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME POLY BD RESIN PART B
PRODUCT NO. EMC85B
SUPPLIER PDM NEPTEC LTD
 4-6 ALTON BUSINESS CENTRE
 OMEGA PARK
 ALTON
 HAMPSHIRE
 GU34 2YU
 +44 (0) 1420 85848
CONTACT PERSON MIKE FELLOWS

2 HAZARDS IDENTIFICATION

Harmful by inhalation. Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation and skin contact.

CLASSIFICATION Xn;R20. R42/43. Xi;R36/37/38.

3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content | Classification |
|--------------------------------|-----------|------------|---------|----------------------------|
| METHYLENEDIPHENYL DIISOCYANATE | 247-714-0 | 26447-40-5 | 30-60% | Xn;R20 R42/43 Xi;R36/37/38 |

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Provide fresh air, warmth and rest, preferably in a comfortable upright sitting position. Get medical attention if any discomfort continues. If respiratory problems, artificial respiration/oxygen.

INGESTION

DO NOT INDUCE VOMITING! Immediately rinse mouth and provide fresh air. Get medical attention immediately!

SKIN CONTACT

Remove affected person from source of contamination. Immediately remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Water spray, fog or mist. Foam. Powder.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Use pressurised air mask if product is involved in a fire.

UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

SPECIFIC HAZARDS

Fire creates: Irritating gases/vapours/fumes of Hydrogen cyanide (HCN). Nitrous gases (NOx).

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

When dealing with a spillage, please consult the section relating to suitable protective measures. Wear necessary protective equipment. Stop leak if possible without risk. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

POLY BD RESIN PART B

USAGE PRECAUTIONS

Persons with impaired lung functions should not handle this preparation. Persons susceptible for allergic reactions should not handle this product. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Keep in original container. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name | Std | LT - ppm | LT - mg/m3 | ST - ppm | ST - mg/m3 |
|--------------------------------|-----|----------|-----------------|----------|-----------------|
| METHYLENEDIPHENYL DIISOCYANATE | WEL | | 0.02 mg/m3(Sen) | | 0.07 mg/m3(Sen) |

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level.

HAND PROTECTION

Use protective gloves made of: Rubber, neoprene or PVC. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved, tight fitting safety glasses where splashing is probable.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|--------------------|--------------------|--------------------------------|-----------------|
| APPEARANCE | Viscous Liquid | | |
| COLOUR | Orange | | |
| ODOUR | Musty (mouldy). | | |
| SOLUBILITY | Insoluble in water | | |
| MELTING POINT (°C) | <15 | RELATIVE DENSITY | 1.24 @ 20 °c |
| BULK DENSITY | 1240 kg/m3 | VISCOSITY | 55 mPas @ 25 °c |
| FLASH POINT (°C) | CC (Closed cup). | AUTO IGNITION TEMPERATURE (°C) | >260 |

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers. Reacts strongly with strong acids, bases, organic chemicals and certain metal combinations.

HAZARDOUS DECOMPOSITION PRODUCTS

High temperatures generate: Toxic gases/vapours/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO). Hydrogen cyanide (HCN).

11 TOXICOLOGICAL INFORMATION

TOXIC DOSE 1 - LD 50 >2000 mg/kg (oral rat)

POLY BD RESIN PART B

TOXIC CONC. - LC 50 490 mg/l/4h (inh-rat)

GENERAL INFORMATION

No specific health warnings noted.

INHALATION

Harmful by inhalation. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.
May cause sensitisation by inhalation.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

Irritating to skin. Prolonged or repeated exposure may cause severe irritation.

EYE CONTACT

Irritating to eyes.

Other Health Effects

This substance has no evidence of carcinogenic properties.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment. The polymer is expected to be of low toxicity.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

| | | | |
|----------------------|-------------------------------------|------------------|-----|
| | No transport warning sign required. | | |
| ROAD TRANSPORT NOTES | Not Classified | | |
| RAIL TRANSPORT NOTES | Not Classified. | | |
| SEA TRANSPORT NOTES | Not Classified. | | |
| AIR TRANSPORT NOTES | Not Classified. | | |
| ADR CLASS | Not classified for transportation. | MARINE POLLUTANT | No. |

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS

METHYLENEDIPHENYL DIISOCYANATE

RISK PHRASES

| | |
|-----------|---|
| R20 | Harmful by inhalation. |
| R36/37/38 | Irritating to eyes, respiratory system and skin. |
| R42/43 | May cause sensitisation by inhalation and skin contact. |

SAFETY PHRASES

| | |
|--------|---|
| P4 | Contains isocyanates. See information supplied by the manufacturer. |
| S37 | Wear suitable gloves. |
| S38 | In case of insufficient ventilation, wear suitable respiratory equipment. |
| S45 | In case of accident or if you feel unwell, seek medical advice immediately (show label where possible). |
| S24/25 | Avoid contact with skin and eyes. |

POLY BD RESIN PART B

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 1988.

ENVIRONMENTAL LISTING

Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980. Rivers (Prevention of Pollution) Act 1961.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION COMMENTS

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

ISSUED BY

Helen O'Reilly

REVISION DATE JUNE 2007

REV. NO./REPL. SDS GENERATED 3

SDS NO. 10908

RISK PHRASES IN FULL

R20 Harmful by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin.

R42/43 May cause sensitisation by inhalation and skin contact.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.